


Stainless Steel Tubing

"Annealed" Welded and Seamless Tubing



- Stocked in 20 foot random lengths
- Alloys stocked include types 304, 304-L, 316-L, and 317-L. Other corrosion resistant alloys are available.
- "Annealed" tubing is used when the specifications referenced below are required. This tubing is primarily used for instrumentation, heat exchangers and in some ornamental applications. Welded "annealed" tubing is available per ASTM A 249, ASME SA-249 and ASTM A 29 and is stocked to 4" OD and available up to 8" OD. Seamless "annealed" tubing is available per ASTM 213, ASME SA-213 and ASTM A 269 and available up to 6" OD.

| Outside Diameter | Wall Thickness | Lbs/Ft | T304 Part Number | T304L Part Number | T316L Part Number | T317L Part Number |
|------------------|----------------|--------|------------------|-------------------|-------------------|-------------------|
| $\frac{3}{16}$ | .028 | .010 | | 567141 | | |
| $\frac{1}{4}$ | .035 | .080 | 143515 | 219609 | 144236 | |
| $\frac{1}{4}$ | .049 | .105 | 143523 | | | |
| $\frac{1}{4}$ | .065 | .128 | 143531 | | | |
| $\frac{5}{16}$ | .065 | .180 | 513859 | | | |
| $\frac{3}{8}$ | .035 | .127 | 143557 | 219510 | 143816 | |
| $\frac{3}{8}$ | .049 | .171 | 143565 | | | |
| $\frac{3}{8}$ | .065 | .215 | 143573 | 594114 | 255786 | |
| $\frac{3}{8}$ | .083 | .260 | | | 594470 | |
| $\frac{7}{16}$ | .028 | .123 | 144121 | | | |
| $\frac{1}{2}$ | .028 | .141 | 144139 | | | |
| $\frac{1}{2}$ | .035 | .174 | 144147 | 143581 | 143840 | |
| $\frac{1}{2}$ | .049 | .236 | 246622 | 143599 | 143858 | |
| $\frac{1}{2}$ | .065 | .302 | | 517405 | 268860 | |
| $\frac{1}{2}$ | .083 | .380 | | 594122 | | |
| $\frac{5}{8}$ | .035 | .221 | 219227 | 118714 | 562573 | 221397 |
| $\frac{5}{8}$ | .049 | .301 | | | | |
| $\frac{5}{8}$ | .065 | .389 | | 143638 | | |
| $\frac{5}{8}$ | .083 | .570 | | | 601945 | |
| $\frac{3}{4}$ | .035 | .267 | 219251 | 268284 | | |
| $\frac{3}{4}$ | .049 | .376 | | 143654 | 118772 | |
| $\frac{3}{4}$ | .065 | .490 | 144171 | 143662 | 255825 | |
| $\frac{3}{4}$ | .083 | .600 | | | 604943 | |
| $\frac{3}{4}$ | .095 | .610 | | | 594172 | |
| $\frac{7}{8}$ | .049 | .440 | 591899 | | | |
| 1 | .035 | .360 | 219308 | | | |
| 1 | .049 | .498 | 231237 | | | |
| 1 | .065 | .649 | 144189 | 143688 | 270079 | |
| 1 | .120 | 1.200 | | | 602307 | |
| 1 $\frac{1}{4}$ | .062 | .823 | | | 272225 | |
| 1 $\frac{1}{4}$ | .065 | .813 | | | | 496879 |
| 1 $\frac{1}{4}$ | .083 | .813 | | | | 475344 |
| 1 $\frac{1}{4}$ | .120 | 1.500 | | 422757 | | |

Note: Widths may be mill edge. Lengths may be random. Dimensions are in inches. All weights are approximate. Sizes not shown may be available upon request.