


## Nominal Pipe Size Dimensions By Schedule



Nominal Pipe Size	Outside Diameter	Sch 5s	Sch 10	Sch 10s	Sch 20	Sch 30	Std. Wt.	Sch 40	Sch 40s	Sch 60	Extra Strong	Sch 80	Sch 80s	Sch 100
1/8	.405			<b>.049</b>			.068	.068	<b>.068</b>		.095	.095	<b>.095</b>	
1/4	.540			<b>.065</b>			.088	.088	<b>.088</b>		.119	.119	<b>.119</b>	
3/8	.675			<b>.065</b>			.091	.091	<b>.091</b>		.126	.126	<b>.126</b>	
1/2	.840	<b>.065</b>		<b>.083</b>			.109	.109	<b>.109</b>		.147	.147	<b>.147</b>	
3/4	1.05	<b>.065</b>		<b>.083</b>			.113	.113	<b>.113</b>		.154	.154	<b>.154</b>	
1	1.31	<b>.065</b>		<b>.109</b>			.133	.133	<b>.133</b>		.179	.179	<b>.179</b>	
1 1/4	1.66	<b>.065</b>		<b>.109</b>			.140	.140	<b>.140</b>		.191	.191	<b>.191</b>	
1 1/2	1.90	<b>.065</b>		<b>.109</b>			.145	.145	<b>.145</b>		.200	.200	<b>.200</b>	
2	2 3/8	<b>.065</b>		<b>.109</b>			.154	.154	<b>.154</b>		.218	.218	<b>.218</b>	
2 1/2	2 7/8	<b>.083</b>		<b>.120</b>			.203	.203	<b>.203</b>		.276	.276	<b>.276</b>	
3	3 1/2	<b>.083</b>		<b>.120</b>			.216	.216	<b>.216</b>		.300	.300	<b>.300</b>	
3 1/2	4	<b>.083</b>		<b>.120</b>			.226	.226	<b>.226</b>		.318	.318	<b>.318</b>	
4	4 1/2	<b>.083</b>		<b>.120</b>			.237	.237	<b>.237</b>		.337	.337	<b>.337</b>	
5	5 9/16	<b>.109</b>		<b>.134</b>			.258	.258	<b>.258</b>		.375	.375	<b>.375</b>	
6	6 5/8	<b>.109</b>		<b>.134</b>			.280	.280	<b>.280</b>		.432	.432	<b>.432</b>	
8	8 5/8	<b>.109</b>		<b>.148</b>	.250	.277	.322	.322	<b>.322</b>	.406	.500	.500	<b>.500</b>	.594
10	10 3/4	<b>.134</b>		<b>.165</b>	.250	.307	.365	.365	<b>.365</b>	.500	.500	.594	<b>.500</b>	.719
12	12 3/4	<b>.156</b>		<b>.180</b>	.250	.330	.375	.406	<b>.375</b>	.562	.500	.688	<b>.500</b>	.844
14		<b>.156</b>	.250	<b>.188</b>	.312	.375	.375	.438	<b>.375</b>	.594	.500	.750	<b>.500</b>	.938
16		<b>.165</b>	.250	<b>.188</b>	.312	.375	.375	.500	<b>.375</b>	.656	.500	.844	<b>.500</b>	1.031
18		<b>.165</b>	.250	<b>.188</b>	.312	.438	.375	.562	<b>.375</b>	.750	.500	.938	<b>.500</b>	1.156
20		<b>.188</b>	.250	<b>.218</b>	.375	.500	.375	.594	<b>.375</b>	.812	.500	1.031	<b>.500</b>	1.281
22		<b>.188</b>	.250	<b>.218</b>	.375	.500	.375		<b>.375</b>	.875	.500	1.125	<b>.500</b>	1.375
24		<b>.218</b>	.250	<b>.250</b>	.375	.562	.375	.688	<b>.375</b>	.969	.500	1.219	<b>.500</b>	1.531
26			.312		.500		.375		<b>.375</b>		.500		<b>.500</b>	
28			.312		.500	.625	.375		<b>.375</b>		.500		<b>.500</b>	
30		<b>.250</b>	.312	<b>.312</b>	.500	.625	.375		<b>.375</b>		.500		<b>.500</b>	
32			.312		.500	.625	.375	.688	<b>.375</b>		.500		<b>.500</b>	
34			.312		.500	.625	.375	.688	<b>.375</b>		.500		<b>.500</b>	
36		<b>.250</b>	.312		.500	.625	.375	.750	<b>.375</b>		.500		<b>.500</b>	
40							.375		<b>.375</b>		.500		<b>.500</b>	
42							.375		<b>.375</b>		.500		<b>.500</b>	
48							.375		<b>.375</b>		.500		<b>.500</b>	

Thicknesses for stainless steel products are specified by ANSI B36.19 and are shown in bold face type.

Thicknesses for carbon steel products are specified by ANSI B36.10 and are shown in regular type.

Thicknesses shown under Sch 40s for sizes 14" -24" and 30" are specified by MSS SP-43.

All other thicknesses shown under Sch 40s and Sch 80s for sizes 14" and larger are not specified by any standard.

Alaskan will use schedule thicknesses shown for all sizes not specified by a standard unless otherwise directed.

Dimensions are in inches.