




# Socket-Welding Fittings Continued




Coupling



Half Coupling



Reducing Coupling



Cap

- Wall thickness, center-to-center and center-to-end dimensions will meet or exceed the applicable specifications.
- Class 150 threaded fittings conform to ANSI B 16.3, Class 3000 threaded fittings conform to ANSI B 16.11.
- Fittings are available in non-standard sizes and most corrosion resistant alloys.
- Mating ends of the fittings can be threaded or finished in a combination of ends when required.
- Crosses available upon request.
- Block pattern fittings available in all corrosion resistant alloys.
- Class 6000 also available.

## Class 3000

Nominal Pipe Size	D(coup)	E(half coup)	F(red. coup.)	G(Caps)
1/8	1	1	1	11/16
1/4	1	1	1	11/16
3/8	1	1 1/16	1	3/4
1/2	1 1/8	1 1/4	1 1/8	7/8
3/4	1 3/8	1 3/16	1 3/8	1
1	1 1/2	1 5/8	1 1/2	1 1/16
1 1/4	1 1/2	1 5/16	1 1/2	1 3/16
1 1/2	1 1/2	1 3/4	1 1/2	1 1/4
2	2 1/8	2 1/4	2	1 1/2
2 1/2	2 1/8	2 5/16	2 1/2	1 1/2
3	2 1/8	2 3/8	3	1 3/4
4	2 1/4	2 5/8	4	1 7/8